

Alligator Clamps



Alligator clamps

ALLIGATOR/CROCODILE CLAMPS					
Picture	Max. current*	Length	Weight	Max. wire size	Connection
	40A	80 mm	25 gr	4 mm ²	 With bow to crimp
	80A	125 mm	60 gr	10 mm ²	
	100A	160 mm	105 gr	35 mm ²	
	300A	160 mm	160 gr	35 mm ²	
	500A	165 mm	215 gr	35 mm ²	
	600A	160 mm	225 gr	35 mm ²	
	800A	150 mm	310 gr	50 mm ²	
	900A	165 mm	310 gr	50 mm ²	
	1000A	150 mm	320 gr	50 mm ²	
	1000A	165 mm	350 gr	50 mm ²	
	750A	180 mm	360 gr	50 mm ²	
	950A	180 mm	370 gr	50 mm ²	

* Maximum current rating according to DIN 72553

* Screwed connections are with M6 screw and lug / for 80A version with M4

ORDERING CODE FOR ALLIGATOR CLIPS

Example:
CRC-FI-600A-RED

“Crocodile Clamp” _____

Insulation: _____

FI – Fully Insulated

PI – Partially Insulated (= insulated handles)

Maximum Current: _____

- 40 A
- 80 A
- 100 A
- 300 A
- 500 A
- 600 A
- 750 A
- 800 A
- 900 A
- 950 A
- 1000 A

Color: _____

BLA – Black

RED – Red

Remarks:

- 500A, 950A and angled 1000A versions only available in fully insulated version
- Ordering codes for 1000A, angled versions are: CRC-FI-A-1000A-BLA and CRC-FI-A-1000A-RED